

AXIS S3008 Recorder

Compact recorder with integrated switch for UHD surveillance

AXIS S3008 Recorder is a compact recorder with an integrated PoE switch for up to 8 cameras. It provides reliable recording thanks to the surveillance-grade hard drive. This high-performance recorder offers gigabit uplink for video recordings in ultra-high definition. Including a 3-year warranty and optional 2-year extended warranty, it is supported only by the AXIS Companion video management software and mobile app.

- > [Compact recorder with integrated PoE switch](#)
- > [Easy to install and operate](#)
- > [Surveillance-grade hard drive](#)
- > [USB port for exporting video](#)
- > [Up to 5-year warranty](#)



AXIS S3008 Recorder

Models	AXIS S3008 Recorder 2 TB AXIS S3008 Recorder 4 TB	Casing	Aluminum and plastic casing Color: Black
Storage	2 TB: 2 TB, surveillance class HDD 4 TB: 4 TB, surveillance class HDD	Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 10–85% RH (non-condensing)
Video		Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH
Recording	Qualified for recording up to 8 video sources with a total recording rate up to 160 Mbit per second	Connectors	Rear side: 8x RJ45 10BASE-T/100BASE-TX PoE 1x RJ45 10BASE-T/100BASE-TX/1000BASE-T DC input Side: 1x USB 3.0
Video compression	H.264 (MPEG-4 Part 10/AVC), H.265 (MPEG-H Part 2/HEVC) Depending on camera support	Approvals	EMC: CISPR 24, CISPR 35, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCC1 Class A Safety: IEC/EN 62368-1, UL 62368-1 Environment: IEC 60068-2-1, IEC 60068-2-14, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-6, IEC 60068-2-78, IEC/EN 60529 IP3X
Resolution	Supports all camera resolutions	Sustainability	PVC free
Frame rate	Supports all camera frame rates	Dimensions	180 x 180 x 53 mm (7 1/16 x 7 1/16 x 2 1/16 in)
Audio streaming	One-way audio recording depending on camera support	Weight	2 TB: 1310 g (2.89 lb) 4 TB: 1350 g (2.98 lb)
Audio compression	AAC Depending on camera support	Included accessories	AXIS Mains adapter 48V DC 90W (01508-001), installation guide
Network		Optional accessories	AXIS TS3001 Recorder Mount
Network function	NTP server	Video management software	AXIS Companion available on axis.com/vms
Security	Password protection, digest authentication, user access log, centralized certificate management, signed firmware, secure boot, IEEE 802.1x (EAP-TLS) network access control	Warranty	Axis 3-year warranty and a 2-year AXIS Extended Warranty option, see axis.com/warranty
Supported protocols	IPv4/v6, HTTP, SSL/TLS, QoS SFTP, SMTP, Bonjour, UPnP™, DNS, NTP, TCP, UDP, IGMP, ICMP, DHCP, ARP, SSH	Environmental responsibility: axis.com/environmental-responsibility	
System integration			
Application Programming Interface	AXIS Video Hosting System (AVHS) with One-Click Connection		
Events & alarms			
Event triggers	Hard drive error, hard drive temperature warning, CPU temperature warning, fan error, PoE budget exceeded		
General			
Supported devices	Axis network cameras and encoders with firmware 8.40 or later		
Input	Power supply: 50–60 Hz, 100–240 V AC, max 90 W Recorder: 1.88 A, 48 V DC, max 90 W		
Output	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 0, Class 1, Class 2, and Class 3 65 W total PoE power budget		