

AXIS T96B05 Outdoor Housing

AXIS T96B05 Outdoor Housing enables mounting of AXIS P39 Series network cameras outside of vehicles and rolling stock, such as buses, trams and emergency vehicles. The enclosure is PVC-free, and made of impact-resistant polymer and aluminum base plate. AXIS T96B05 complies with strict regulatory demands of the transportation industry.

- > Enclosure for mounting onboard cameras outside vehicles and rolling stock
- > Compliant to IP66/IP67, IP6K9K, NEMA 250 Type 4X and IK09
- > Operating temperature -40 °C to 60 °C (-40 °F to 140 °F)



AXIS T96B05 Outdoor Housing

Supported products	AXIS P3904-R Mk II Network Camera and AXIS P3905-R Mk II Network Camera with 3.6 mm, 6 mm and 8 mm lenses	EMC EN 55032 Class A, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, EN 50121-4, EN 50121-3-2, IEC 62236-4, ECE R10 rev.05 (E approval), EN 50498
Lens	Maximum horizontal field of view^a 87° with 3.6 mm M12 lens 52° with 6 mm M12 lens 40° with 8 mm M12 lens	Safety IEC/EN 62368-1, IEC/EN 60950-22 (CB certificate), EN 45545
Camera angle adjustment	With 3.6 mm M12 lens Pan: 0° Tilt: 0° With 6 mm M12 lens Pan: ±20° Tilt: 0°–15° Rotation: ±175° With 8 mm M12 lens Pan: ±30° Tilt: 0°–15° Rotation: ±175°	Environment IEC/EN 61373 Category 1 Class B, IEC 60529 IP66/IP67, NEMA 250 Type 4X, IEC/EN 62262 IK09, ISO 20653 IP6K9K, EN 50155:2017 Class OT2/ST2 (EN 50155:2007 Class TX), IEC 60721-3-5 Class 5M3 (vibration and shock), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78
General		Dimensions
Casing	IP66/IP67, IP6K9K, NEMA 4X-rated, IK09 impact resistant aluminum and polymer enclosure Color: white NCS S 1002-B	Height: 56 mm (2 1/4 in) ø 150 mm (5 7/8 in)
Sustainability	PVC free	Weight
Operating conditions	-40 °C to 60 °C (-40 °F to 140 °F) Humidity: 10–100% RH (condensing)	540 g (1.2 lb) with AXIS P39 Series network camera
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)	Included accessories
Approvals	These approvals apply together with supported AXIS P39 Series network cameras	Installation guide, drill template Top cover tool Allen key Lens tool kit
		Warranty
		Axis 3-year warranty, see www.axis.com/warranty

a. Lenses for AXIS P39 Series network cameras

Environmental responsibility:

axis.com/environmental-responsibility