



## 2 Port HDMI 2.0, USB 2.0 & Audio Cable KVM Switch

No.: 42345

Switch between 2 HDMI equipped PCs from one keyboard, mouse and monitor

### Description

- Control two HDMI equipped PCs from a single keyboard, mouse and monitor
- Switch via the unit's push button control, software or keyboard hot keys
- Supports HDMI 2.0 signals, up to 4K 60Hz
- Integrated cables for quick, hassle-free installation
- 2 Year Warranty

The Lindy 2 Port HDMI 2.0, USB 2.0 & Audio KVM Switch is a compact solution for providing access and control over two HDMI equipped PCs from a single keyboard, mouse and monitor. With integrated cables, this switch can be easily connected directly to the system, with no need for purchasing additional cables and saving time on the installation. Support for resolutions up to 4K Ultra HD 60Hz ensures the optimum image quality, perfect for high graphical content in gaming setups, video editing or dual system control workstations. The audio output port on the main unit also allow users to connect headphones or speaker to add immersive 2CH audio and a microphone, while additional USB peripherals can be integrated with a USB hub.

The KVM switch features multiple switching options including a push button control (with 1.5m cable), hotkey and software switching to provide simple, reliable control for the user, great for both professional and first time users.

Please note: this KVM switch can be used with DisplayPort or Mini-DisplayPort equipped computers using a DisplayPort to HDMI or Mini-DisplayPort to HDMI converter

### Technical details

#### Specifications

- AV Interface: HDMI
- Console Interfaces: USB
- Interface Standard: HDMI 2.0, USB 2.0
- Maximum Resolution: 4096x2160@60Hz 4:4:4 8bit
- HDCP Support: HDCP 2.2
- Supported Audio: Analogue Stereo
- Separate Audio Ports: 2 x 3.5mm (Female)
- Serial Interface: -
- Console Number: 1

- Max Number PC/Server: 2
- Cascadable: -
- Switching Method: Push Button, Hotkey Switching & Software
- 19" Rack Mountable: -
- Special Features: Supports USB 2.0 Hubs And Device Sharing, Active LED Indicators

#### **Connectors**

- Console Interfaces: HDMI Type A (Female), 2 x USB 2.0 Type A (Female), 2 x 3.5mm (Female)
- PC/Server Interfaces: 2 x HDMI (Male), USB 2.0 Type A (Male), 2 x 3.5mm (Male) 1.2m Integrated Cables
- Other Interfaces: -
- Power: -

#### **Physical Properties**

- Dimensions (approx.) WxDxH: 97x25x82.18mm (3.82x0.98x3.24in)
- Housing Material: Plastic
- Net Weight: 0.436kg (0.96lb)
- Operating Temperature: 0°C - 40°C (32°F - 104°F)
- Storage Temperature: -20°C - 60°C (-4°F - 140°F)
- Humidity: 0 - 90% RH (non-condensing)
- Power Requirements: 5V
- Colour: Black

#### **Miscellaneous**

- Packaging Type: Carton Box
- Packaging Dimensions: 160x60x250mm (6.3x2.36x9.84in)
- Gross Weight: 0.517kg (1.14lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH & California Proposition 66

#### **Package Contents**

- HDMI KVM Switch
- Lindy Manual

#### **Purchasing Information**

- No.: 42345
- EAN: 4002888423458