





SP 7 Dirt Inox

With level sensor and integrated prefilter: the SP 7 Dirt Inox submersible dirty water pump copes with up to 15,500 l/h of dirty water in demanding drainage tasks.



1 Ceramic face seal.

- For an extra long lifetime.

2 Level Sensor

- For continuously variable definition of the switch-on and switch-off points of the pumps.

3 Quick Connect

- Connection thread for quick and uncomplicated connection of 1", 1 1/4" and 1 1/2" hoses.

4 Designed for dirty water

- Reliable pumping of water with dirt particles up to 30 mm in size.



SP 7 Dirt Inox

Technical data

Order no.	1.645-506.0	
EAN code	4054278060453	
Max. motor rating	W	750
Max. flow rate	l/h	15500
Delivery height / Max. pressure	m / bar	8 / 0.8
Max. immersion depth	m	7
Max. grain size	mm	30
Residual water height	mm	35
Delivery temperature, max.	°C	35
Weight without accessories	kg	6.65
Dimensions (L × W × H)	mm	238 × 287 × 354
Connection thread	G1 1/2	
Power cable	m	H07RN8-F / 10

Equipment

Comfortable carrying handle	■
Hose connection piece	1", 1 1/4", 1 1/2"
Easy hose connection thanks to Quick Connect	■
Switching between manual/automatic operation	Switch on the pump
Level sensor: Continuous switching level definition	■
Integrated stainless steel pre-filter	■
Ceramic face seal.	■

■ Included in the scope of supply.

SP 7 DIRT INOX 1.645-506.0



1



2

		Order no.					Price	Description	
Suction hoses									
Suction hose available in bulk	1	6.997-346.0						Vacuum-resistant spiral hose can be cut to length for connection to submersible, garden, submersible pressure pumps and high-pressure pumps.	<input type="checkbox"/>
Miscellaneous									
Fabric hose set	2	2.997-100.0						Space-saving hose set with a flexible fabric hose, including stainless steel hose clamp for connecting to submersible pumps. Ideal as a feed hose for water removal in the event of flooding.	<input type="checkbox"/>

Available accessories.