Product data sheet

Specifications



linear switch - iSSW - 1 C/O - 20A - 250 V AC - 3 positions

A9E18073

Main

Range of product	Acti 9
Product name	Acti9 iSSW
Product or component type	Linear switch
Device short name	iSSW
Device application	Electrical circuit control
Contacts type and composition	1 C/O
[Ue] rated operational voltage	250 V AC 50/60 Hz
Standards	IEC 60669-1 IEC 60947-5-1

Complementary

[le] rated operational current	20 A	
Control type	Toggle 3 positions	
Marking	1 - 0 - 2	
Mounting mode	Clip-on	
Mounting support	DIN rail	
9 mm pitches	2	
Height	82 mm	
Width	18 mm	
Depth	75 mm	
Colour	White	
Electrical durability	AC-22: 30000 cycles cos Phi = 0.8	
Connections - terminals	Staggered tunnel terminal (downside) 2 cable(s) 0.52.5 mm² flexible Staggered tunnel terminal (downside) 2 cable(s) 0.52.5 mm² rigid without cable end	
Wire stripping length	9 mm	
Tightening torque	1 N.m	

Environment

IP degree of protection	IP20 conforming to IEC 60529	
Tropicalisation	2	

Pollution degree	3
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-2050 °C
Ambient air temperature for storage	-4070 °C

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	45.0 g
Package 1 Height	6.6 cm
Package 1 width	1.8 cm
Package 1 Length	8.2 cm
Unit Type of Package 2	S03
Number of Units in Package 2	108
Package 2 Weight	5.816 kg
Package 2 Height	30.0 cm
Package 2 width	30.0 cm
Package 2 Length	40.0 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	12
Package 3 Weight	592.0 g
Package 3 Height	7.8 cm
Package 3 width	9.8 cm
Package 3 Length	23.3 cm

Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty 18 months	
--------------------	--