



### Main

Range of product	Acti 9
Product or component type	Linear switch
Switch application	Electrical circuit control
Device short name	ISSW
Contacts type and composition	1 C/O
[Ue] rated operational voltage	250 V AC 50/60 Hz
Standards	IEC 60669-1 IEC 60947-5-1

### Complementary

[Ie] rated operational current	20 A 250 V AC 50/60 Hz
Control type	Toggle 3 positions
Marking	1 - 0 - 2
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	2
Height	82 mm
Width	18 mm
Depth	75 mm
Colour	White
Electrical durability	AC-22 : 30000 cycles
Connections - terminals	Staggered tunnel terminal (downside) 2 cable(s) $\leq$ 2.5 mm <sup>2</sup> flexible Staggered tunnel terminal (downside) 2 cable(s) $\leq$ 2.5 mm <sup>2</sup> rigid without cable end Staggered tunnel terminal (downside) 2 cable(s) $\geq$ 0.5 mm <sup>2</sup> flexible Staggered tunnel terminal (downside) 2 cable(s) $\geq$ 0.5 mm <sup>2</sup> rigid without cable end
Wire stripping length	9 mm downside
Tightening torque	1 N.m downside

### Environment

tropicalisation	2
pollution degree	3
relative humidity	95 % at 55 °C
ambient air temperature for operation	-20...50 °C
ambient air temperature for storage	-40...80 °C

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

### Contractual warranty

Warranty period	18 months
-----------------	-----------