



CIRCUIT BREAKER 400V 6KA, 2-POLE, C,
2A, D=70MM

Similar to image

Technical data:

| | | |
|--|----|---------------------------------|
| Overvoltage class | | 3 |
| type of voltage | | AC/DC |
| Tripping characteristic class | | C |
| Degree of pollution | | 3 |
| Mounting depth | mm | 70 |
| Energy limiting class | | 3 |
| Number of poles | | 2 |
| Number of pitch units for width | | 2 |
| Product function / n-switching | | No |
| Supply voltage frequency / rated value | Hz | 50 |
| Switching capacity current / in accordance with IEC 60947-2 / rated value | kA | 30 |
| Breaking capacity current / acc. to EN 60898 / rated value | kA | 6 |
| Supply voltage / for AC / rated value | V | 400 |
| Current / for AC / rated value | A | 2 |
| Protection class IP | | IP20, with connected conductors |
| Product extension / can be installed / supplementary device | | Yes |
| power loss | | - |

| | | |
|---|---|---------------------------------------|
| Operational voltage Um | | - |
| rated current In | | - |
| Rated make-break capacity Icn | | - |
| Rated service short-circuit breaking capacity Ics | | - |
| Rated ultimate short-circuit breaking capacity Icu | | - |
| Tripping characteristics Number | | - |
| Tripping characteristic/-class Conventional tripping current I2, (x In) | | - |
| rated current In IEC, DIN/VDE | | - |
| Tripping characteristic/-class Test current I4, hold (x In) | | - |
| rated current In / IEC, DIN/VDE | | |
| • at 30 Cel | A | 2 |
| • at 40 Cel | A | 1.88 |
| • at 45 Cel | A | 1.806 |
| • at 50 Cel | A | 1.73 |
| • at 55 Cel | A | 1.656 |
| • at 60 Cel | A | 1.58 |
| Resistance against shock / according to IEC 60068-2-27 | | 150m/s ² at 11ms half-sine |

Certificates/approvals:

General Product Approval



CQC

[IMQ](#)

[KETI](#)

[ROSTEST](#)



UL



VDE

Declaration of Conformity

[Manufacturer](#)

Shipping Approval



BUREAU
VERITAS



DNV



GL



LRS



RINA

other

[other](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)



<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SY6202-7/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY6202-7



last change:

Nov 3, 2011