SIEMENS

Product data sheet




CIRCUIT BREAKER 400V 6KA, 2-POLE, C, 4A, D=70MM

Similar to image

Technical data:		
Overvoltage class		3
type of voltage	_	AC/DC
Tripping characteristic class		С
Degree of pollution		3
Mounting depth	mm	70
Energy limiting class		3
Number of poles		2
Number of pitch units for width	_	2
Product function / n-switching		No
Supply voltage frequency / rated value	Hz	50
Switching capacity current / in accordance with IEC 60947-2 / rated value	kA	30
Breaking capacity current / acc. to EN 60898 / rated value	kA	6
Supply voltage / for AC / rated value	V	400
Current / for AC / rated value	А	4
Protection class IP		IP20, with connected conductors
Product extension / can be installed / supplementary device		Yes
power loss		-

Operational voltage Um		-
rated current In	-	-
Rated make-break capacity Icn		-
Rated service short-circuit breaking capacity lcs		-
Rated ultimate short-circuit breaking capacity Icu		-
Tripping characteristics Number	-	-
Tripping characteristic/-class Conventional tripping current I2, (x In)		
rated current In IEC, DIN/VDE		-
Tripping characteristic/-class Test current I4, hold (x In)		-
rated current In / IEC, DIN/VDE		
• at 30 Cel	А	4
• at 40 Cel	А	3.76
• at 45 Cel	А	3.612
• at 50 Cel	А	3.46
• at 55 Cel	А	3.312
• at 60 Cel	А	3.16
Resistance against shock / according to IEC 60068-2-27		150m/s ² at 11ms half-sine
Certificates/approvals:		




http://www.siemens.com/lowvoltage/mall


Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/5SY6204-7/all


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY6204-7

CAx-Online-Generator

http://www.siemens.com/cax







last change:

Nov 3, 2011