

# PHILIPS

## Floodlight

ProjectLine

20 W

3000K warm white light

Integrated motion sensor



8719514954427



## Professional quality for your project

Water tight, robust LEDs for outdoor use. ProjectLine floodlight supports energy saving, and is robust with its metal material and weather protection. The integrated motion sensor is adaptable in reach, time and light sensitivity. Ideal to light up areas in front/back of (public) buildings, such as car parks, driveways, gardens or working locations, when you need it.

### Sustainable choice

- Save energy from the moment you flick the switch

### Choose for the high-quality light

- You can trust what the Philips packaging is saying

# Highlights

## Energy efficient

All Philips energy savers save energy from the moment you flick the switch. During their lifetime they use fewer kW and thus also result in a lower energy

bill. The level of energy saving differs per lamp type and technology.

## Reliable quality

Philips keeps its promises about lamp performance. You can trust what the Philips packaging is saying about light output, lifetime and wattage equivalence to incandescent lamps.

# Specifications

## Design and finishing

- Optical cover/lens type: Glass

## Durability

- Ambient temperature range: -25 to +40 °C

## Environmental

- Sustainability rating: -

## Guarantee

- Warranty period: 2 years

## Light characteristics

- Colour rendering index (CRI): 80
- Color Code: 830 warm white
- Correlated Color Temperature (Nom): 3,000
- Init. Color Rendering Index Tolerance: 0
- Initial chromaticity: (0.440, 0.403)
- SDCM <6
- Lamp family code: LED
- Light source engine type: LED
- Light source replaceable: No
- Luminaire light beam spread: 110°
- Luminous Flux: 1,800 lm
- Luminous flux tolerance: +/-10%
- Optic type outdoor: Symmetrical
- Performance ambient temperature Tq: 25 °C
- Upward light output ratio: 0

## Other characteristics

- CE mark: CE mark
- ENEC mark: -
- Photobiological risk: Photobiological risk group 1 @ 200mm to EN62471
- Photobiological risk specification: 0.2 m

## Power

- Input Voltage: 220 to 240
- Inrush current: 0.45
- Inrush time: 0.066
- Power Factor (Fraction): 0.9

## Power consumption

- Power Consumption: 20 W
- Power consumption tolerance: +/-10%

## Technical specifications

- Cable: Cable 0.3 m without plug
- Connection: Flying leads/cables
- Control gear failure rate at median useful life 35000 h: 5 %
- Driver/power unit/transformer: -
- Driver included: Yes
- Flammability mark: For mounting on normally flammable surfaces
- Ingress protection code: IP65 | Dust penetration-protected, jet-proof
- Line Frequency: 50 or 60
- Lumen maintenance at median useful life\* 35000 h: 70
- Mech. impact protection code: IK05 | 0.7 J
- Number of gear units: Unit
- Number of products on MCB of 16 A type B: 104
- Protection class IEC: Safety class I
- Surge Protection (Common/Differential): EN61547 (L-L 1 kV, L-G 2 kV)

8719514954427

**Packaging dimensions and weight**

- EAN/UPC - product: 8719514954427
- Net weight: 0.410 kg
- Gross weight: 0.429 kg
- Height: 6.000 cm
- Length: 15.800 cm
- Width: 14.500 cm
- Material number (12NC): 911401862584



Issue date: 2022-10-24  
Version: 0.164

© 2022 Signify Holding. All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

[www.lighting.philips.com](http://www.lighting.philips.com)