

Model: AK-ND-21



1.7 mm 19.0 v 1.58 A 30 w

InclusionMAXMD221Product typeAC/DC adapterCompabilie withAC/D CadpaterCompabilie withAC/D CadpaterDellDellcatedDellDellDellcatedDellSupply voltage100-250 VPower consumption< 1ACompabilie withS0 %Compabilie withS0 %Dutput voltage19 VOutput voltage1.2 mOutput contector5.5 x 1.7 mOutput contector5.5 x 1.7 mOutput contector5.5 x 1.7 mOutput contector30 WContectorSoft statYesYesContectorSoft statYesYesContectorNoneContectorNoneSoft statYesSoft statYesContectorNoneSoft statYesSoft statYesSoft statYesSoft statYesSoft statSoft statYesSoft statSoft statYesSoft statYesSoft StatSoft statSoft StatSoft StatSoft StatYesSoft StatSoft		
Compatible with SeriesAcer / Dell / Packard BellGelicatedSeriesDedicatedDell®OneWire verificationYesSupply volage10.025 VGenerationSelowCompatible with EfficiencySelowCompatible with Output volage19.VOutput volage19.VOutput connectorS.S.A.T.A.TCompatible with Dower compatibleICC 83Compatible with Compatible with Dower compatibleNoneCompatible with SelowSelowCompatible with Dower compatibleYesCompatible with SelowYesCompatible with SelowYesCompatible with SelowYesCompatible with SelowNoneCompatible with SelowYesCompatible with SelowNoneCompatible with SelowYesCompatible with SelowNoneCompatible with SelowSelowCompatible with SelowNoneCompatible with	Product code	AK-ND-21
SeriesDedicatedDell® OneWire verificationYes100-250 V100-250 VComper consumption< 1a		
Dell & OneWire verificationYesSupply voltage100-250 VPower consumption< 1A		
Supply voltage100-250 VPower consumption<1A		
Power consumption< 1AEfficiency> 80 %Output voltage19 VI output voltage1.58 AI output contecto5.5 x 1.7 mmOutput connecto5.5 x 1.7 mmI output connectoS.5 x 1.7 mmI output connectoYesI output connectoYesI output connectoYesI output connectoYesI output connectoYesI output connectoNoneI output connectoNoneI output connectoSoI output connectoSecI output connectoSoI output connectoSo <td></td> <td></td>		
Efficieny> 80 %Output voltage19 VOutput voltage1.58 AOutput conletto1.58 AOutput conletto5.5 x 1.7 mmOutput conletto30 WPower intelIEC 03Output conletto6.00 APower intelIEC 03Output conlettoYesOutput conlettoYesOutput conlettoYesOutput conlettoYesOutput conlettoYesOutput conlettoYesOutput conlettoYesOutput conlettoYesOutput conlettoYesOutput conlettoNoneOutput conlettoNoneOutput conlettoSoft statPower cable includedNoneOutput conlettoBlackOutput conlettoSoft statProduct collSoft statProduct collSoft statProduct collNoneOutput collSoft statProduct collSoft statProduct collSoft statProduct collSoft statProduct size (Lx W xH)Soft statProduct size (Lx W xH)Soft statOutput collSoft statProduct size (Lx W xH)Soft statOutput collSoft statProduct size (Lx W xH)Soft statSoft statSoft statProduct size (Lx W xH)Soft statSoft statSoft statProduct size (Lx W xH)Soft statProduct size (Lx W xH)Soft stat <tr< td=""><td></td><td></td></tr<>		
Output voltage19 VOutput amperage1.58 AOutput condector5.5 N.1.7 mmOutput connector5.5 N.1.7 mmOutput connector30 WPower inletIEC C8Ground Maximum power80 WGround Maxinam powerYesGround Maxinam powerYesOutput connectorYesOutput connectorYesOutput connectorYesOutput connectorYesOutput connectorYesOutput connectorYesOutput connectorNoneOutput connectorNoneOutput connectorNoneOutput connectorSoft statYesSoft statYesYesOutput connectorNoneOutput connectorNoneOutput connectorSoft statYesSoft statY		
Output amperage1.58 AOutput condelor1.2 mOutput connector5.5 x 1.7 mmOutput connector30 WPower initelIEC C8IEC C8Mechanical switchMechanical switchNoneOutput connectorYesIEC C9YesIEC C9NoneIEC C9NoneIEC C9NoneIEC C9SecontectorIEC C9YesIEC C9YesIEC C9SecontectorIEC C9SecontectorIEC C9SecontectorIEC C9SecontectorIEC C9SecontectorIEC C9SecontectorIEC C9SecontectorIEC C9SecontectorIEC C9SecontectorIEC C9Secontector </td <td></td> <td></td>		
Outlet cord length1.2 mOutput connector5.5 x 1.7 mmOutput connector30 WPower inletIEC C8Mechanical switchNoneMechanical switchNoneGround wireYesSoft statYesOUPYesOUPYesOUPYesOUPYesOUPYesOUPYesOUPYesOUPYesOUPYesOUPYesOUPYesOUPYesOUPYesOUPYesOUSB connectorNoneOUSB connectorNonePower cable includedNoMaterialABSOUSD NGreen LEDOUSD NSono NTemperatarEcoloxProduct size (L x W x H)100 x 90 x 38 mmOutput size (L x W x H)130 gAlex Size (L X W xH)130 gCE compatibilityYes		
Output connects5.5 x 1.7 mmMaximum powe30 WPower inletIEC C8Mechanical switchNoneMechanical switchYesGround wireYesSoft stattYesPower on DOVPYesMachanical SwitchYesMachanical SwitchYesMachanical SwitchYesMachanical SwitchYesMachanical SwitchYesMachanical SwitchYesMachanical SwitchYesMachanical SwitchNoneMaterialABSMaterialSacAMaterialSonoMateria		
Maximum power30 WPower intelECC 8Mechanical switchNoneMechanical switchYesGround wireYesSoft startYesPower on DOPPYesPower cable includedNonePower cable includedNonePower cable includedSoProduct colorBlackDisplayNonePower DisplayNonePower on DisplayNoneProduct size (Lx W x H)99 x36 x 26.5 mmPackage size (Lx W X H)130 gPackage size (Lx W X H)130 gPackage size (Lx W X H)179 gPower on DOP SizeYes		1.2 m
Power interIEC C8Mechanical switchNoneGround wireYesCalled Called		
Mechanical switchNoneGround wireYesSoft statYesPower Soft statYesGaland Soft Soft Soft Soft Soft Soft Soft Soft		
Ground wireYesGoddYes		IEC C8
Soft startYesOVPYes	Mechanical switch	None
OVPYesImage: Constant of the second of the	Ground wire	Yes
OCPYesImage: Constant of the second of the	Soft start	Yes
OPPYesCONDYesCONDYesCONDYesCONDNoneCONDNoneCONDNoneCONDSolat <td>OVP</td> <td>Yes</td>	OVP	Yes
OTPYesCODEYesCODEYesCODEYesCODENonCODENonPower cable includedNoPower cable includedABSCODEBacklight colorProduct colorGreen LEDCODESonCODESonProduct Size (L x W xH)SonProduct size (L x W xH)SonSonSonCodeSonProduct size (L x W xH)Son	OCP	Yes
SCPYesCompositionNoneDSB connectorNonePower cable includedNoPower cable includedSaMaterialBasCompositionGreen LEDDisplayNoneProduct CompositionSo °CProduct Size (L x W x H)So × Sa ×	OPP	Yes
Ferrite filterYesI CloseNonePower cable includedNoPower cable includedABSI CloseBlackI CloseGreen LEDI CloseNoneI CloseSolooo hI Close	OTP	Yes
USB connectorNonePower cable includedNoPower cable includedABSProduct onoBlackProduct onoGreen LEDPower cable includedNonePower cable included10000 hPower cable included5.50 °CProduct size (L x W x H)89 x 36 x 26.5 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x 38 mmPackage size (L x W x H)100 x 90 x	SCP	Yes
Power cable includedNoIncludedABSIncludedBlackIncludedBlackIncludedGreen LEDIncludedNoneIncluded10000 hIncludedS - 50 °CIncludedEcoBoxIncludedS - 30 °CIncludedS - 30 °	Ferrite filter	Yes
MaterialABSProduct colorBlackBacklight colorGreen LEDDisplayNoneInternational10000 hInternational5 - 50 °CInternationalSo - 50 °CInternationa	USB connector	None
Product colorBlackBacklight colorGreen LEDDisplayNoneMTBE100000 hTemperature5 - 50 °CPackageEcoBoxProduct size (L x W x H)89 x 36 x 26.5 mmPackage size (L x W x H)190 x 90 x 38 mmPackage size (L x W x H)130 gGross weight179 gCE compatibilityYes	Power cable included	No
Backlight colorGreen LEDDisplayNoneMTBF100000 hTemperature5 - 50 °CPackageEcoBoxProduct size (L x W x H)89 x 36 x 26.5 mmPackage size (L x W x H)190 x 90 x 38 mmPackage size (L x W x H)130 gGross weight179 gCE compatibilityYes	Material	ABS
DisplayNoneMTBF100000 hTemperature5 - 50 °CProduct size (L x W x H)89 x 36 x 26.5 mmProduct size (L x W x H)190 x 90 x 38 mmMet weight130 gGross weight179 gCE compatibilityYes	Product color	Black
MTBF10000 hCender5 - 50 °CPackageEcoBoxProduct size (L x W x H)89 x 36 x 26.5 mmPackage size (L x W x H)190 x 90 x 38 mmNet weight130 gGross weight179 gCE compatibilityYes	Backlight color	Green LED
Temperature5 - 50 °CPackageEcoBoxProduct size (L x W x H)89 x 36 x 26.5 mmPackage size (L x W x H)190 x 90 x 38 mmNet weight130 gGross weight179 gCE compatibilityYes	Display	None
PackageEcoBoxProduct size (L x W x H)89 x 36 x 26.5 mmPackage size (L x W x H)190 x 90 x 38 mmImage: Size (L x W x H)130 gSize (L x W x H)179 gCE compatibilityYes	MTBF	100000 h
Product size (L x W x H)89 x 36 x 26.5 mmPackage size (L x W x H)190 x 90 x 38 mmNet weight130 gGross weight179 gCE compatibilityYes	Temperature	5 - 50 °C
Package size (L x W x H)190 x 90 x 38 mmNet weight130 gGross weight179 gCE compatibilityYes	Package	EcoBox
Net weight130 gGross weight179 gCE compatibilityYes	Product size (L x W x H)	89 x 36 x 26.5 mm
Gross weight179 gCE compatibilityYes	Package size (L x W x H)	190 x 90 x 38 mm
CE compatibility Yes	Net weight	130 g
	Gross weight	179 g
FCC compatibility Yes	CE compatibility	Yes
	FCC compatibility	Yes
RoHS compatibility Yes	RoHS compatibility	Yes
REACH compatibility Yes	REACH compatibility	Yes





3

Description

Akyga® AK-ND-21 is a **notebook dedicated power supply** for devices powered with **19V/1.58A**, **30W** power and **5.5*1.7 mm** plug.

The cord of the power adapter has been equipped with a high-quality **ferrite core** that prevents and protects devices from any possible mode currents and high frequency noise. A set of protectors (OVP, OTP, OPP, SCP and OCP) guarantees 100% secure, stable work both powered device and the power supply. Additional safety for the equipment is provided by the soft start technology, which neutralizes the shock of the first stroke of current during the device startup.

All Akyga power supplies are provided in an environmentally friendly EcoBox.

A power supply dedicated to Acer, Dell and Packard Bell laptops.

We encourage you to use our notebook power adapter search engine.