



## **IPC 1U-10240**

The **IPC 1U-10240** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 1U-10240** provides the possibility to mount maximal eight 2.5" or two 3.5" internal hard drives. Two standard 40mm fans guarantee an optimal cooling.

Additional extras like easily reachable USB connectors and the universal slot bracket complete this total package.

## Specifications

Motherboard	Mini ITX, Flex-ATX, mATX <sup>1</sup> , µATX <sup>1</sup> , ATX <sup>1</sup> maximal motherboard size WxD: 305mm x 191mm, 12" x 7.5" <small>(<sup>1</sup>maximal 191mm mounting depth)</small>
Drive Bays	5.25" external: 2* 3.5" internal: 2* 2.5" internal: 8*
Front Connectors	USB 3.0: 1 USB 2.0: 1
Cooling System	Internal: 2x 40mm <small>(included, 3pin (4pin connector))</small>
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity Alert
Power Supply	1U Server PSU, FLEX-ATX
Material	1.0/1.2mm Steel
Packing Units	Shipping Unit: 1 Piece Pallet: 42 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887099
EAN-Code	4260133126206
Scope of Delivery	Screw Set Mounting bracket for FLEX-ATX PSU
Features	2x 40mm fan included USB 3.0 and USB 2.0 as block connector Universal ATX I/O plate 1x Riser slot

\*can vary by using several mounting options

## Dimensions and Weight

	Cage	Case	Package
Height	44.5mm	44.5mm	110mm
Width	433mm	482mm	545mm
Depth	400mm	428mm	560mm

Weight (net): 5.00Kg  
Weight (gross): 6.60Kg

## Power supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	-

**Without**

**Certification:**

